



Cement Tile

Installation Materials

CONTACT

Phone: (512) 260-9111

Email: info@rusticotile.com

Address: 251 Honeycomb Mesa

Leander, Texas 78641 USA

Website: RusticoTile.com

SEALER SYSTEM



We offer an easy 2-step sealer system for properly protecting Cement Tile. Step 1 sealer serves as a primer to the Step 2 topcoat sealer. Topcoat sealer protects the surface of the tile with scratch-resistance & UV protection. It also provides a final desired sheen and seals the grout.

Step 1: Crest Natural Penetrating Sealer

- \$139/Gallon
- 600 sf coverage per gallon
- Environmentally-friendly, Low VOC/Odor
- 10-minute dry time with easy application

Step 2: Crest Natural or Gloss Topcoat Sealer

- \$139/Gallon
- 600 sf coverage per gallon
- Natural or High Gloss Finishes Available
- Environmentally-friendly, Low VOC/Odor
- Very high abrasion resistance

THINSET



We offer high-quality thinset for your Cement Tile installation. It's important to use proper thinset with handmade Cement tile to avoid unnecessary issues in the future. In most orders, thinset can ship with your tile at no extra shipping cost.

Crest Gran Formato Thinset

- \$30/bag
- 30-35 sf coverage per bag (approximately)
- Overcomes irregularities in tile thickness
- Superior flexibility and bond strength
- Suitable for concrete slab or backer-board substrates

CRACK PREVENTION & WATERPROOFING MEMBRANE



Apply crack prevention membrane to existing hairline cracks (on a slab) or to cement board joints. This helps prevent hairline cracks from appearing on your tile floor.

Full coverage application is recommended on new slabs. This product doubles as a waterproofing membrane. The membrane is needed as full coverage in wet outdoor areas.

Crest 2510 Acrylic Membrane

- \$95 per 1-gallon, 45 sf coverage (approximately)
- \$230 per 3.5-gallon, 135 sf coverage (approximately)
- Apply at 30 mils wet film thickness